

PT158

Panel Mount Printer

Applications:

Industrial Instrument

Medical Instrument

Electric Weight Scale

Analyser

Automotive Equipment

Handheld Equipment



Easy paper loading



Technical Data:

Print Method	Direct line thermal
Resolution	8 dots/mm, 384 dots/line
Paper / Printing Width	57.5+0.5 mm / 48 mm
Printing Speed	Up to 50 mm/sec
Interface	RS232 (1200bps ~ 57600bps)
	Optional Bluetooth
Command Code	ESC Command Set
Fonts	ASC II International
Characters per Line	32 (24*12) / 32 (16*12) / 48 (16*8) (H x W dot)
Character Chinese	16 (24*24) / 24 (16*16) (H x W dot)
Bar-Code	CODE39,93,128 / EAN8,13 / UPC-A,E / ITF / CODABAR
Downloadable	Fonts, Graphics, Logos and additional Bar - Codes
Voltage Supply	DC +6V ~ +9V 3A (Peak 5A)
MTBF	50 kms (Printing ratio: 15% or less)
Roll Diameter	40 mm (Approx. 18 meters)
Housing Material	PC (different colors possible)
Weight	100 g (paper roll not include)
Dimensions (mm)	W76.8 * D77.4 * H47.6 (Control board included)
Environment	0 ~ 50°C, 20 ~ 85%RH (no condensation)



MEGADATA INDUSTRIAL, Inc.

TEL: +886 4 2265 3311 FAX: 2261 3770

www.posjet.com.tw megadata@ms21.hinet.net